

Product data sheet

Item No. 96.233.4004.1

Cable assembly RST20i3K1-S 25P 40SW

Connection cable, male - free end, length 4m, RST20i3, 3 pole, 250V/20A, cable type H05VV, cross section 2,5 mm², color of coding: black



Item No.	96.233.4004.1
EAN	4015573760509
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *P*	Stecker male
.0	lichtgrau light grey	PE	N
.1	schwarz black		

Weitere Daten siehe Katalog
further data see catalog

Typ/type: RST2013K1-S 25P .. GL = lichtgrau/light grey
SW = schwarz/black

Teile - Nr. part - no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
96.233.XX04.F	XX in dm-Schritten	96.233.1004.1 = 10dm/L= 1000mm	RST2013K1-S 25P 10SW
U6.233.XX04.F	XX in m-Schritten	U6.233.1204.1 = 12 m/L=12000mm	RST2013K1-S 25P X12SW

Beschreibung nach DIN 1925/Tolerance system acc. to DIN 1925. This DIN standard describes the envelope principle. According to the average principle, the deviations of form and position are limited by the size tolerances.		Typus 02 Schaltzeichen- und Bezeichnungssymbol nach DIN EN 60417 mit Sonderzeichen. Conform to IEC 60417 document U6-10M-EN/03 (list of prohibited / derestricted characters) to be deleted!	
First tolerance notch Beschriftung nach 010 - Drawing, kein modifizierendes 010 - Drawing, no market modifications allowed	2006 Tag/Date Name	T Zeichnung Nr./Drawing No.	Index 96.233.0404.0 01K
Made in mm/Dimensions are in mm			
		KONFEKT_LEITUNG Stecker-freies Ende / male-free end pre-assembled cable	