

Data Sheet | Item Number: 734-426


Strain relief plate; for female and male connectors; 1 part; Pin spacing 3.5 mm; light gray

<https://www.wago.com/734-426>



Color: ■ light gray

Similar to illustration



Dimensions in mm

The arrangement of the attachments for cable ties allows single conductors or multi-core cables to be secured in different ways. The width of the cable ties must correspond to the hole dimensions of the strain relief plates shown above.

Physical data

Width	55 mm / 2.165 inches
Height	1.87 mm / 0.074 inches
Depth	37 mm / 1.457 inches

Mechanical data

Suitable	for standard male and female connectors (2.5 mm; 3.5 mm; 5 mm; 7.5 mm pin spacing)
----------	--

Material data

Note (material data)	Information on material specifications can be found here
Color	light gray
Fire load	0.08 MJ
Weight	2.7 g

Commercial data

Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454163143
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 734-426 ↓

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2010.85 KB	↓


CAD/CAE-Data

CAD data
2D/3D Models 734-426 ↓

CAE data
ZUKEN Portal 734-426 ↓

Installation Notes

Installation



Strain relief plates for factory or in-the-field assembly

Application



Strain relief plate, for factory assembly
1-conductor female connector, 2.5 mm pin
spacing, light gray,
12-pole, with strain relief plate
733-112/034-000

Application



Strain relief plate, for factory assembly
1-conductor female connector, 2.5 mm pin
spacing, light gray,
2-pole, with strain relief plate
(733-102/032-000)