

Starter STARTER FS-22 0024433



Product features

•

- Reliable and fast-starting, - Suitable for temperatures from -20 to +80 degrees C, - For single and twin operation

UK C E

PRODUCT OVERVIEW

| Product name | STARTER FS-22 |
|---------------------------------------|---|
| Technology | Accessory |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail |
| ETIM Class | EC000260 |
| E-number FI | 4045119 |
| E-number SE | 7902065 |
| E-number Norway | 3843402 |
| Wattage (W) | 4 |
| Non-reclosure Voltage | 70V |
| Nominal Line Voltage Single Operation | 110-130V |
| Nominal Line Voltage Tandem Operation | 220-240V |
| Product EAN number | 5410288244334 |

DATA TABLE

| General data | |
|---------------------------------------|---|
| Product name | STARTER FS-22 |
| Technology | Accessory |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail |
| ETIM Class | EC000260 |
| E-number FI | 4045119 |
| E-number SE | 7902065 |
| E-number Norway | 3843402 |
| Optical data | |
| Adjustable chromaticity | Ν |
| Electrical data | |
| Wattage (W) | 4 |
| Non-reclosure Voltage | 70V |
| Nominal Line Voltage Single Operation | 110-130V |
| Nominal Line Voltage Tandem Operation | 220-240V |



Starter STARTER FS-22 0024433

| Physical data | |
|---------------------------------------|-------------------|
| Nominal Product Height (mm) | 36 |
| Max. Lamp Diameter (mm) - D | 21.5 |
| Weight (kg) | 0.005 |
| | |
| Packaging | |
| Single packaging type | Without Packaging |
| Product EAN number | 5410288244334 |
| Packaging single length / height (cm) | 2.08 |
| Packaging single width (cm) | 2.08 |
| Packaging single depth (cm) | 3.89 |
| DUN14 (inner) | 25410288244338 |
| Units per inner package | 250 |
| Packaging inner length / height (cm) | 22.67 |
| Packaging inner width (cm) | 12.21 |
| Packaging inner depth (cm) | 23.33 |
| DUN14 (outer) | 15410288244331 |
| Units per outer package | 2500 |
| Packaging outer length / height (cm) | 63.1 |
| Packaging outer width (cm) | 49.9 |
| Packaging outer depth (cm) | 24.3 |