



Socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, base with screw terminals and finishing set, claw fixing, cream

100-66600



Compound socket outlet (base and finishing set) with pin earthing. The base is equipped with screw terminals and claw fixing. The socket outlet also has shutters and a flush-mounting depth of 28.5 mm. Colour: cream

This article is protected by at least one patent (or patent application). For more info on patents, see www.niko.eu/innovation.



Technical data

Socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, base with screw terminals and finishing set, claw fixing, cream.

- Colour: cream
- Colour RAL (approximately): 1013
- Colour NCS (approximately): NCS S 1005-Y10R
- Type of fastening:
 - with claws that can be rotated open using screws with a slotted screw head (slot 0.8 x 5 mm), for mounting in a flush-mounting box with grip surfaces
 - depth of engagement of claws: 31 mm
 - claws turn back completely when loosened
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Protection degree standalone: IP20
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: CEBEC
- Marking: CE

This product consists of several components. Below you will find an overview of the technical features of all components.

Base for socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, 16 A, screw terminals.

- Flush-mounting frame type:
 - 1 mm-thick metal
 - galvanized on all sides after cutting, even on the cut edges
 - with 4 grooves with screw hole of 7 mm
 - with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm for mounting on panels
- Type of fastening:
 - simple mounting in a flush-mounting box with grip surfaces
 - with claws that rotate open using screws with a combination screwhead (Pz2 or slot 1 x 5.5 mm), for mounting in a flush-mounting box with grip surfaces
 - engagement depth of claws: 23.5 mm
 - claws turn back completely when loosened
- Base end border: 4 rectangular openings (7 x 2.5 mm) which, if the flush-mounting box protrudes from the plasterwork, can compensate for a margin of between 1 and 1.2 mm, so that the faceplate can still butt up perfectly against the wall
- Terminal with permanent screws: each connector block is equipped with cage clamps with permanent screws
- Terminals location: top of the base
- Terminal wire connection: screw terminals
- Terminals wire capacity: 2 x 2.5 mm²
- Terminals with screw driver slot : every screw is fitted with a screwdriver slot that prevents the screwdriver from sliding off the screwhead
- Terminal screw head: combination screwhead (screw PZ2 or slot 1 x 5.5 mm)
- Wire stripping length: 14 mm
- Minimum flush-mounting depth: 28.5 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: CEBEC

Finishing set for socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, cream.

- Colour: cream
- Colour RAL (approximately): 1013
- Colour NCS (approximately): NCS S 1005-Y10R
- Surface treatment: coloured in mass
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)
 - all plastic components are halogen-free
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: CEBEC

Wiring diagram

