

# Threefold faceplate, 71 mm centre distance, Niko Pure steel black coated

**161-76700**



Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure.  
Niko Pure steel black coated



## Technical data

Threefold faceplate, 71 mm centre distance, Niko Pure steel black coated.

- Threefold faceplate for three switches.
- Colour faceplate: steel black coated
- Colour RAL (approximately): 9004
- Colour NCS (approximately): NCS S 9000-N
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of steel. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upper frame is enamelled black
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
  - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 83 mm x 225 mm x 8.9 mm
- Certification marks: CE, NF, KEMA, ÖVE, SEMKO, VDE
- Marking: EU