

START Downlight Flat 206 SQ IP44 1650LM 830 DIM 0054126



Features

- START Downlight Flat 206 SQ IP44 1650LM 830 DIM

Product Overview

Product name	START Downlight Flat 206 SQ IP44 1650LM 830 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
Fixture luminous flux (lm)	1650
Luminaire efficacy (lm/W)	97
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9003
IP rating	IP44/20

START Downlight Flat 206 SQ IP44 1650LM 830 DIM 0054126

IK rating	IK06
Product EAN number	5410288541266
Warranty	5 years
Built in presence detector	NONE
Virtual assistant compatibility	N/A
Dimming method	Mains: leading / trailing edge

Photometry

Technical drawings