



Features

- LiFeSafe PRO TS 2000 IP65 W EM3 NM DA. LiFeSafe PRO Twin Spot IP65 W EM3 NM DA is a wall mounted DALI addressable Twin Spot Non-Maintained 3Hr emergency duration with LiFePO4 battery. 2 x 1000lm per head, 14W system power, IK08, IP65, Class II electrical construction. 6-year warranty.

Product Overview

Product name	LIFESAFE PRO TS 2000 IP65 W EM3 NM DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Wall surface mounted
Light source included	0038862
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	143
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	2000
Luminous flux (emergency) (lm)	2000
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP65
IK rating	IK08



LIFESAFE PRO TS 2000 IP65 W EM3 NM DA  
**0038862**

Product EAN number	5410288388625
Warranty	6 years