

17VBS-2005: Straight adapter VBS manifold 20x3/4"



Commercial information

Connection piece for the Henco VBS distributor. Can only be used with the VBS05 or VBS06. This fitting is made of brass with a stainless steel sleeve.

Basic unit dimensions

| | |
|------------|----------|
| Height | 50 mm |
| Length | 31 mm |
| Width | 31 mm |
| Net weight | 0.080 kg |

Certificates

DVGW Wasser, KIWA, KOMO, ATG, ÖN EN 21003-2/-3, ÖVGW Wasser, ETA, STF, QB (CSTBat), AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

| | | | |
|------------------------------------|-------------------------------------------------------|----------------------------------|------------------------|
| Material connection 1 | Brass | Bend radius | 0 Millimetre |
| Material quality connection 1 | CuZn40Pb2 (CW617N) | Outer pipe diameter connection 1 | 20 Millimetre |
| Surface protection connection 1 | Untreated | Length | 31 Millimetre |
| Surface treatment connection 1 | Untreated | Length of connection 1 | 37 Millimetre |
| Material connection 2 | Brass | Working length connection 1 | 37 Millimetre |
| Material quality connection 2 | CuZn40Pb2 (CW617N) | Length of connection 2 | 18 Millimetre |
| Surface protection connection 2 | Untreated | Working length connection 2 | 18 Millimetre |
| Surface treatment connection 2 | Untreated | Wrench width | 0 Millimetre |
| Shape | Straight | Wrench width union nut | 0 Millimetre |
| Reducing | ✗ | Medium temperature (continuous) | -10 70 Degrees celsius |
| Eccentric | ✗ | Max. operating pressure at 20 °C | 16 Bar |
| System specific | ✓ | Standard Dimension Ratio (SDR) | 0 |
| Connection 1 | Press sleeve | | |
| Nominal diameter connection 2 | 3/4 inch (20) | | |
| Connection 2 | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) | | |
| Main colour fitting | Brass | | |
| Material sealing | Ethylene-propylene diene monomer rubber (EPDM) | | |
| With buffer stud | ✓ | | |
| High tensile strength | ✗ | | |
| With thermal insulation | ✗ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✗ | | |
| Capped | ✗ | | |
| With connection indicator | ✗ | | |
| With drain valve | ✗ | | |
| With de-aerator | ✗ | | |
| FM quality mark | ✗ | | |
| LPCB quality mark | ✗ | | |
| ULC quality mark | ✗ | | |
| UL quality mark | ✗ | | |
| DIN-CERTCO certificate | ✗ | | |
| VdS quality mark | ✗ | | |
| With approval for TÜV | ✗ | | |
| DVGW quality mark for gas | ✗ | | |
| DVGW quality mark for water | ✓ | | |
| KIWA certified | ✓ | | |
| Gastec QA mark | ✗ | | |
| KOMO certified | ✓ | | |
| Type approval according to BBR/EKS | ✗ | | |