

Features

- Simple and slick integral design with no driver box and without any visible screws Improved thermal resistance with in-track driver, ideal for retail applications
- Extremely precise light beams due to the high-quality lenses
- Die-cast aluminium body, Beam angle: 36°, additional lenses 24° and 54° beam angle included in the packaging,
- Textured white finishing colour
- Light color temperature: 3000K, warm white
- System power: 14W, Fixture lumen output: 1650lm, efficacy: 118lm/W, Ra90 typical, LED chromacity: 3 step MacAdam ellipse LED source (SDCM3), IR/UV free light source without heat radiation
- Operating voltage 220-240V / 50-60Hz, DALI dimmable driver, ultra low LED flickering rate (5% or less)
- Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet.
- Compatible with OneTrack Electrical protection: Class II.
- Degree of protection: IP20, suitable for indoor environment only
- Horizontal rotation: 345°, vertical tilt: 90°
- Nominal product dimensions: D.60mmx130mm, lenght of the Adaptor : 198mm.
- 5 years warranty.
- Recycling instructions for extra lens in this product: please contact us for recycling instructions or disposal.

Product Overview




| | |
|---------------------|-------------------------------------------------------------|
| Product name | Pixo Small 1650lm 930 NB MB WB DALI White |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Track mounting |
| General application | Museums & Galleries, Retail, Office, Residential & Consumer |
| ETIM Class | EC001744 |

Light your world

Pixo Small 1650lm 930 NB MB WB DALI White 0004556


| | |
|------------------------------------------|-----------------------------|
| E-number FI | 4279605 |
| Fixture luminous flux (lm) | 1650 |
| Luminaire efficacy (lm/W) | 118 |
| Correlated colour temperature (k) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | 3 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 14 |
| Electrical protection | Class II |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK03 |
| Product EAN number | 5410288045566 |
| Warranty | 5 years |
| Built in presence detector | NONE |
| Virtual assistant compatibility | N/A |
| Dimming method | DALI-2 |

Photometry




Light your world

Pixo Small 1650lm 930 NB MB WB DALI White 0004556



Technical drawings



Data table

GENERAL DATA

| | |
|-----------------------------------------|-------------------------------------------------------------|
| Product name | Pixo Small 1650lm 930 NB MB WB DALI White |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Track mounting |
| Built in presence detector | NONE |
| General application | Museums & Galleries, Retail, Office, Residential & Consumer |
| Operating temperature range (°C) | 1°C...+25°C |

Light your world



Pixo Small 1650lm 930 NB MB WB DALI White 0004556

| | |
|---------------------------------|----------|
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001744 |
| E-number FI | 4279605 |
| Warranty | 5 years |

OPTICAL DATA

| | |
|-----------------------------------|------------|
| Fixture luminous flux (lm) | 1650 |
| Luminaire efficacy (lm/W) | 118 |
| Correlated colour temperature (k) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | 3 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

ELECTRICAL DATA

| | |
|-----------------------------------------------------------------------|-----------------------------|
| Total power consumption (W) | 14 |
| Supply current (A) | 0.06 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x % | 20 |
| Electrical protection | Class II |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI-2 |
| Inrush Current (A) | 10 |
| Inrush Duration (μ s) | 3 |
| Energy Efficiency Class (A->G) of contained light source | E |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 96 |

Light your world

| | |
|---------------------------------|-----|
| Max. products per 13A C Breaker | 125 |
| Max. products per 16A C Breaker | 154 |
| Max. products per 20A C Breaker | 192 |
| Max. products per 10A B Breaker | 60 |
| Max. products per 13A B Breaker | 78 |
| Max. products per 16A B Breaker | 96 |
| Max. products per 20A B Breaker | 120 |

LIFETIME DATA

| | |
|------------------|--------|
| Lifespan L70 B50 | 120000 |
| Lifespan L70 B20 | 120000 |
| Lifespan L70 B10 | 120000 |
| Lifespan L80 B50 | 120000 |
| Lifespan L80 B20 | 120000 |
| Lifespan L80 B10 | 120000 |
| Lifespan L90 B50 | 120000 |
| Lifespan L90 B20 | 120000 |
| Lifespan L90 B10 | 120000 |

PHYSICAL DATA

| | |
|-------------------------------|------------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Other |
| Diffuser material | None |
| Reflector finish | High-gloss |
| Nominal Product Length (mm) | 130 |
| Nominal Product Diameter (mm) | 60 |
| Weight (kg) | 0.426 |

PACKAGING

| | |
|---------------------------------------|---------------|
| Product EAN number | 5410288045566 |
| Packaging single length / height (cm) | 24.0 |
| Packaging single width (cm) | 9.5 |



Pixo Small 1650lm 930 NB MB WB DALI White

0004556

| | |
|--------------------------------------|----------------|
| Packaging single depth (cm) | 19.3 |
| DUN14 (inner) | 15410288045563 |
| Units per outer package | 16 |
| Packaging outer length / height (cm) | 50.5 |
| Packaging outer width (cm) | 40.0 |
| Packaging outer depth (cm) | 41.0 |

SAFETY DATA

| | |
|-------------------------------------|------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | 1-25 |
| Special purpose lamp | No |
| Dry applications use only | No |
| Suitable for household illumination | No |



Light your world