Technical data sheet

Profile rail, 17 mm slot, perforated, black

Item number: 1104293

Middle C profile rail for cable routing, in connection with clamp clips with hammer-head foot Can also be used as a suspended construction for cable tray systems.



CE 17 H E30 E90

St Steel

P135 PES135 - Polyester

Master data


Item number	1104293
Type	CML3518P0400 SW
Description 1	Profile rail
Description 2	perforated, slot 17mm
Manufacturer	OBO
Dimension	400x35x18
Colour	Jet black; RAL 9005
Material	Steel
Surface Surface standard	PES135 - Polyester
Smallest sales unit	10
Unit of quantity	Piece
Weight	30 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,7256 kg CO2e / 1 Piece

Technical data sheet

Profile rail, 17 mm slot, perforated, black

Item number: 1104293

Dimensions



Length	400 mm
Width	35 mm
Height	18 mm

Technical data

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	25 mm
Maintain electrical functions	yes
Material thickness	1.25 mm
With perforation	yes
With toothing	no
Profile shape	C profile
ROHS-conformant	yes
Rustproof steel, pickled	no
Slot width	17 mm
Static value Iy	0.41 cm⁴
Static value Iz	1.81 cm⁴
Static value Wy	0.41 cm³
Static value Wz	1.03 cm³