


Socket outlet with side earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, plug-in terminals, red

199-66915



Socket outlet with side earthing and shutters. This socket outlet has a flush-mounting depth of 28.5 mm and is equipped with plug-in terminals and screw fixing. Includes finishing set. A faceplate in the colour of your choice must be ordered separately. Colour: red.

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the flush-mounting box.

Faster and easier installation:

- all connections terminals are located at the top of the base:


Niko quality:

- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop
- metal base is held firmly in place, even on uneven walls, doesn't break and is not subject to stress cracking (small ruptures)
- firm metal claws with a large engagement depth (31 mm) remain fixed when mounted and can be screwed tightly to ensure that the socket outlets can remain fixed in the wall for a longer time and to avoid the mechanisms should become warped

Technical data

Socket outlet with side earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, plug-in terminals, red.

- Colour: red
- Colour RAL (approximately): 3001
- Surface treatment: coloured in mass
- Type of fastening:
 - with screws for simple fixing in a flush-mounting box with grip surfaces



- Base end border: 4 rectangular openings (7 x 2.5 mm) which, if the flush-mounting box protrudes from the plasterwork, can compensate for a margin of between 1 and 1.2 mm, so that the faceplate can still butt up perfectly against the wall
- Terminal wire connection: plug-in terminals
- Wire stripping length: 14 mm
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)
 - all plastic components are halogen-free
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE

Wiring diagram

