


RANA NEO Surface 1200
RANA NEO 3600LM S 1200 830 DALI 1L WHITE
0054224



Product features

- Surface or Suspended LED luminaire with Micro Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1160x187x56mm, White body colour, IP20, IK07, DALI Dimmable, Low LED flicker (+/- 5%), Warm White (3000K) LED Colour Temperature, 3600lm, 30W, 120lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.




PRODUCT OVERVIEW

Product name	RANA NEO 3600LM S 1200 830 DALI 1L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3600
Fixture luminous flux (lm)	3600
Luminous flux (lm)	3600
Luminaire efficacy (lm/W)	120
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288542249

PHOTOMETRY

RANA NEO Surface 1200
RANA NEO 3600LM S 1200 830 DALI 1L WHITE
0054224



TECHNICAL DRAWINGS

