

Single faceplate, Niko Pure liquid black

242-76100



Single faceplate from the range Niko Pure. Niko Pure liquid black.

Technical data

Single faceplate, Niko Pure liquid black.

- Simple faceplate for one switch.
- Colour faceplate: liquid black
- Colour RAL (approximately): 9005
- Colour NCS (approximately): NCS S 9000-N
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of hard-coated polymethyl methacrylate (PMMA). The lower frame is made of dark grey, black coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Surface treatment: coloured in mass
- Surface finishing: glossy
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 83 mm x 83 mm x 8.9 mm
- Certification marks: CEBEC, NF, KEMA, ÖVE, SEMKO
- Marking: EU

