



### Features

- L-shape connection unit for opal diffuser version of Otao Linear range, RAL9003 (white) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 2x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 170x170x50x73mm.

### Product Overview

<b>Product name</b>	OTAO LINEAR CORN-L OPAL 830/840 WH
<b>Technology</b>	LED (3 SDCM)
<b>Cap/Base</b>	N/A
<b>Housing</b>	Aluminium
<b>Mount</b>	Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended
<b>General application</b>	Office, Education
<b>ETIM Class</b>	EC002556
<b>E-number FI</b>	4170598
<b>Fixture luminous flux (lm)</b>	660
<b>Luminaire efficacy (lm/W)</b>	135
<b>Correlated colour temperature (k)</b>	4000
<b>Light colour</b>	Warm White or Neutral White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	3
<b>Beam Angle (°)</b>	110
<b>Glare control</b>	< 28
<b>Photobiological Risk Group</b>	RG0
<b>Total power consumption (W)</b>	4.9
<b>Electrical protection</b>	Class III

## OTAO LINEAR CORN-L OPAL 830/840 WH 0041809

Dimmable	No
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK03
Product EAN number	5410288418094
Warranty	5 years
Dimming method	N/A

### Technical drawings

