


2173002	DATA SHEET	
valid from: 2025-11-27	UNITRONIC® TRAIN MVB 2x2x0.5	

Application

Field of use:	Bus cable for the Multifunction Vehicle Bus (MVB) for serial data communication in railway vehicles. MVB is a component of the Train Communication Network (TCN) and standardized in IEC 61375-3-1.
Performance:	Screened foiled star quad cable, having a nominal impedance of 120 Ω. Designed for transmission rates of 1.5 Mbit/s. The MVB transmits time-critical control signals in real time.
Characteristics:	flame retardant, no flame propagation, halogen free, low smoke density, ozone resistant, UV resistant, oil resistant, fuel resistant, resistant to acids and alkalis
Applications:	MVB, TCN, RS-485 and others



Design

Certification	EN 45545-2: Hazard Level HL1, HL2, HL3 fire prevention acc. to NF F 16-101 Internal: Vehicle Categories A1, A2, B External: Vehicle Categories A2, B Category D for flame propagation Category F0 for smoke density
Conductor	fine-wire stranded tinned copper 0.5 mm ² (19 x 0.185 mm) conductor diameter: ca. 0.92 mm
Insulation	foamed polyolefine core diameter: ca. 2.3 mm
Core identification code	pair 1: red/blue, pair 2: grey/brown
Stranding	cores stranded to star quad
Screen	plastic laminated aluminium foil (overlapping) on top: braid of tinned copper wires (coverage 85 % ± 5 %) diameter over braid: ca. 5.9 mm
Taping	thin non-woven tape (optional)
Outer sheath	cross-linked polymer compound, halogen free and flame retardant acc. to EN 50264-1, EM 104 black, similar RAL 9005 outer diameter: ca. 8.3 mm

Electrical properties at 20 °C

Conductor resistance	max. 40.1 Ω/km
Insulation resistance	min. 5 GΩ x km
Mutual capacitance	max. 46 nF/km (1.5 MHz)
Capacitive coupling	max. 1500 pF/km (1.5 MHz)
Characteristic impedance	120 Ω ± 10% (0.75 MHz - 3 MHz)
Attenuation	max. 15 dB/km (1.5 MHz) max. 20 dB/km (3 MHz)
Near-end cross-talk	min. 45.0 dB/km (0.75 MHz - 3 MHz)
Velocity of propagation	0.74 c
Transfer impedance	max. 20 mΩ/m (20 MHz)
Maximum operating voltage	125 V (not for power purposes)
Test voltage	core/core: 1000 V

Creator: TOGO / PDC	Document: DB2173002EN	Page 1 of 2
Released: ALTE / PDC	Version: 05	

2173002	DATA SHEET	
valid from: 2025-11-27	UNITRONIC® TRAIN MVB 2x2x0.5	

core/screen: 1000 V

Mechanical and thermal properties

Minimum bending radius	fixed installation:	3 x outer diameter
	occasional flexing:	10 x outer diameter
Temperature range	fixed installation:	-40 °C up to +90 °C
Burning load	0.286 kWh/m (calculated value)	
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2	
	flame propagation acc. to IEC 60332-3-25 resp. EN IEC 60332-3-25	
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1	
	acc. to EN 50264-1 appendix B	
Corrosivity of gases	acc. to IEC 60754-2 resp. EN 60754-2	
Smoke density	acc. to IEC 61034-2 resp. EN 61034-2	
Toxicity	acc. to EN 50305	
Weather and UV resistance	acc. to EN 50289-4-17 cables with black sheath are suitable for permanent outdoor use	
Ozone resistance	acc. to EN 50305	
Oil resistance	acc. to EN 50264-1, EM 104	
Fuel resistance	acc. to EN 50264-1, EM 104	
Tests	Test procedures for electrical characteristics and transmission characteristics acc. to EN 50288-1.	
General requirements	These cables are conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and the LV-Directive 2014/35/EU (Low voltage Directive).	
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).	

Creator: TOGO / PDC	Document: DB2173002EN	Page 2 of 2
Released: ALTE / PDC	Version: 05	