

## Product data sheet

Item No. 91.232.3064.1

### Cable assembly GST15I3KS-S 15HW 30SW

geis® Connection cable male - free end; length: 3m; type GST15I3; 3-pole; 250 V / 16 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 3G1,5 , colour: black



|            |               |
|------------|---------------|
| Item No.   | 91.232.3064.1 |
| EAN        | 4049644009938 |
| Order Unit | 25 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | Black  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | Black  |

### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 3                                   |
| Nominal cross section conductor | 1.5 mm²                             |
| Degree of protection (IP)       | IP40                                |
| Wire strip length               | 8 mm                                |
| sheath strip length             | 21 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | S05Z1Z1-F                           |

|                     |                  |
|---------------------|------------------|
| Cable colour        | Black            |
| Cable diameter      | 8 mm             |
| Version of cable    | Male - free end  |
| Type of cord set    | Connection cable |
| Version cable end 1 | GST15i3 plug     |
| Version cable end 2 | Free end         |

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | Yes           |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 3 m |
|--------------|-----|