



Features

- Clip-in opal diffuser to build seamless continuous line for Otao Linear with opal diffuser, 30m length.

Product Overview

Product name	OTAO LINEAR OPAL ROLLED DIFF 30M
Technology	LED (3 SDCM)
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended
General application	Office, Education
ETIM Class	EC002557
E-number FI	4170607
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Housing colour	White
Product EAN number	5410288418216
Warranty	5 years

Data table

GENERAL DATA

Product name	OTAO LINEAR OPAL ROLLED DIFF 30M
Technology	LED (3 SDCM)
Type of accessory	Optical accessory
Housing	PC Polycarbonate

OTAO LINEAR OPAL ROLLED DIFF 30M 0041821

Mount	Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended
General application	Office, Education
Operating temperature range (°C)	5°C...+50°C
ETIM Class	EC002557
E-number FI	4170607
Warranty	5 years

OPTICAL DATA

Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable

ELECTRICAL DATA

Control gear required	No
------------------------------	----

PHYSICAL DATA

Housing colour	White
Weight (kg)	1.75

PACKAGING

Product EAN number	5410288418216
Packaging single length / height (cm)	55.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	55.0
DUN14 (inner)	15410288418213
Units per outer package	5
Packaging outer length / height (cm)	57.0
Packaging outer width (cm)	32.0
Packaging outer depth (cm)	57.0

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-50

OTAO LINEAR OPAL ROLLED DIFF 30M 0041821

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No