

## P-PIPESTOP32: Stop end for pipe Press Ø32



### Commercial information

These fittings offer great advantages with regard to corrosion.

- The body of the fitting consists of brass CW617N.
- The fitting is equipped with a thrust ring to prevent direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- Electrolysis is thus excluded.
- The fitting is equipped with EPDM O-rings and stainless steel press sleeves with 3 control windows.
- To prevent assembly errors, the stainless steel press sleeves are marked with the size and type of press profile that can be pressed.

#### Basic unit dimensions

Height	45 mm
Length	39 mm
Width	39 mm
Net weight	0.129 kg

#### Certificates

ATG, DVGW Wasser, ETA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, SABS, EMI, KIWA

#### Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Outer pipe diameter connection 1	32 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Max. operating pressure at 20 °C	10 Bar
Surface protection connection 1	Untreated	Wrench width	0 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
System specific	✓	Standard Dimension Ratio (SDR)	0
Nominal diameter connection 1	DN 20		
Connection 1	Press sleeve		
Contour code	BE		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	Brass		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✗		
Capped	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		