



### Features

- Reflector replacement modules for Otao Linear reflector versions, 3000K/4000K LED light source included, black finishing, 4 modules per pack.



### Product Overview

Product name	OTAO LINEAR REF BLK 4PCS
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
General application	Office, Education
ETIM Class	EC002556
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 19
Photobiological Risk Group	RG1
Electrical protection	Class III
Dimmable	No
Housing colour	RAL9003
IP rating	IP20
IK rating	IK03

## OTAO LINEAR REF BLK 4PCS 0041807

Product EAN number	5410288418070
Warranty	5 years
Built in presence detector	NONE
Virtual assistant compatibility	N/A
Dimming method	N/A

### Data table

#### GENERAL DATA

Product name	OTAO LINEAR REF BLK 4PCS
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+50°C
Virtual assistant compatibility	N/A
ETIM Class	EC002556
Warranty	5 years

#### OPTICAL DATA

Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

#### ELECTRICAL DATA

Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0

## OTAO LINEAR REF BLK 4PCS 0041807

Electrical protection	Class III
Control gear required	No
Dimmable	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz

### LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	100000

### PHYSICAL DATA

Housing colour	RAL9003
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	Other
Reflector finish	Not Applicable
Weight (kg)	0.25

### PACKAGING

Product EAN number	5410288418070
Packaging single length / height (cm)	29.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	13.0
DUN14 (inner)	15410288418077
Units per outer package	100
Packaging outer length / height (cm)	31.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	29.5

### SAFETY DATA

## OTAO LINEAR REF BLK 4PCS 0041807

---

<b>Glow Wire Test (°C)</b>	650
<b>Optimal operating condition (°C)</b>	5-50
<b>Special purpose lamp</b>	No
<b>Dry applications use only</b>	No
<b>Suitable for household illumination</b>	No