Product data sheet Spirotech

Product name

SpiroCombi -DN80 -Magnet -Flange

Product properties

A steel (microbubble) deaerator and dirt separator with magnet for standard flow rate (1.5 m/s) with a DN50 - DN300 PN16 flange connection

- Combined separation system removes circulating air and microbubbles effectively
- Improve cost control and energy efficiency
- Applicable with 50/50 Ethylene Glycol / Water (Volume)
- $\bullet~$ Very small particles, from 5 μm (= 0.005 mm), are separated and removed
- Including a magnet for extra protection and high efficient removal of magnetite
- Dirt can be discharged while the system is in operation
- No shut-off valves or bypass required
- Constant low pressure drop
- PN16 flange connections
- Connection diameters from DN50 DN300, larger connection diameters on request
- Exceptional guarantee


Article number

BC080FM

Product image



Product dimensions





Product data sheet Spirotech

ETIM product data

| Housing material | Steel |
|------------------------------|----------------|
| With drain valve | Yes |
| Housing material quality | St 37 (1.0254) |
| Backwash filter | No |
| Max. operating pressure | 10 bar |
| KVS value [m3/h] at ΔP 1 bar | 153.4 |
| Variable flow direction | Yes |
| With insulation | No |
| Separator type | Air/dirt |
| Connection | Flange |
| Model | Horizontal |
| Nominal diameter | DN 80 |
| Max. glycol mixture | 50 % |
| Suitable for heating | Yes |
| Suitable for cooling | Yes |
| Construction length | 470 mm |
| Article compression class | PN 10 |

| Surface protection | Lacquered |
|---------------------------------------|-----------|
| Suitable for open system | No |
| Suitable for closed system | Yes |
| Suitable for solar | No |
| With dismountable filter | No |
| Filter volume | 17 |
| Magnet operating principle | Yes |
| With automatic de-aerator | Yes |
| With integrated replenishment automat | No |
| With couplers | No |
| Cleaning possible during operation | Yes |
| Material of connection | Steel |
| Inlet/outlet offset distance | 0 mm |
| Operating principle | Magnet |
| Magnet location | Internal |
| Flange standard | DIN |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website



