



Features


- Recessed mounting frame accessory with trim, made of aluminium, dimensions: 97x1192mm, ceiling cut-out dimensions: 83x1165mm. Finishing colour RAL9003 (white).

Product Overview

Product name	OTAO LINEAR RECESSED FRAME WH
Technology	Non - Electrical Device
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office, Education
ETIM Class	EC002557
E-number FI	4170612
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Electrical protection	Class III
Housing colour	RAL9003
IP rating	OTHER
IK rating	IK03
Product EAN number	5410288418292
Warranty	5 years
Built in presence detector	NONE

OTAO LINEAR RECESSED FRAME WH 0041829

Technical drawings



Data table

GENERAL DATA

Product name	OTAO LINEAR RECESSED FRAME WH
Technology	Non - Electrical Device
Type of accessory	Mounting kit
Housing	Aluminium
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+50°C
ETIM Class	EC002557
E-number FI	4170612
Warranty	5 years

OPTICAL DATA

Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable

ELECTRICAL DATA

Electrical protection	Class III
Control gear required	No
Max. products per 10A C Breaker	100

OTAO LINEAR RECESSED FRAME WH 0041829

Max. products per 13A C Breaker	100
Max. products per 16A C Breaker	100
Max. products per 20A C Breaker	100
Max. products per 10A B Breaker	100
Max. products per 13A B Breaker	100
Max. products per 16A B Breaker	100

PHYSICAL DATA

Housing colour	RAL9003
IP rating	OTHER
IK rating	IK03
Diffuser finish	Other
Weight (kg)	1.7

PACKAGING

Product EAN number	5410288418292
Packaging single length / height (cm)	122.0
Packaging single width (cm)	6.1
Packaging single depth (cm)	7.8
DUN14 (inner)	15410288418299
Units per outer package	4
Packaging outer length / height (cm)	124.0
Packaging outer width (cm)	14.2
Packaging outer depth (cm)	19.4

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No