

Product data sheet

Item No. 96.452.1004.6

Cable assembly RST20i5KS-S 15P 10TB04

Connection cable, male - free end, length 1m, RST20i5, 5 pole, mains 250V/dimming, 16A, cable type H05VV, cross section 1,5mm<sup>2</sup>, color of coding: turquoise



Item No.	96.452.1004.6
EAN	4015573941939
Order Unit	30 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	
Color of housing inclusive strain relief	Black

**Model**

Number of poles	5
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends



Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	1 m
--------------	-----

**Technical drawing**

Kodierung/Keying 4  
(250V/50V/20A)

\*Z\*

Gesamtlänge/total length

L ± 3%

Schnittlänge/cutting length

1-34 ± 3%

Kabeltype/cable type H05VV-F5G1,5

Teil-Nr. part-no.	L	Beispiel (Farbe: türkisblau) example (colour: turquoiseblue)	Typ type
96.452.XXL.6	XX in dm-Schritten	96.452.1004.6 = 10dm/1 = 100mm	R5120/SKS-S 15P 10T/B04
96.452.XXL.6	XX in m-Schritten	96.452.1004.6 = 12 m/1 = 1200mm	R5120/SKS-S 15P 112/B04

	<b>wieland</b>	Typ <b>KONFEKT_LEITUNG</b>
Wieland Electric AG Wielandstraße 1 73511 Isenhardt Germany	Wieland Electric AG Wielandstraße 1 73511 Isenhardt Germany	© 2010 Wieland Electric AG Alle Rechte vorbehalten Wieland Electric AG ist ein Unternehmen der Wieland Group