

**Features:**

- 7/8" screw connection: Industry-proven connection technology for a large selection of different conductors
- High protection class for safe field applications
- Vibration- and shock-resistant via integrated locking mechanism
- PUR coating

**Technical data**

**Operating Data**

Operating voltage	600 VAC/VDC
Operating current	9 A

**Safety and protection**

Rated impulse withstand voltage	4 kV
Protection type	IP67

**Connection Data**

**Connection 1**

Connection technology	7/8"; 3-pole; angled socket
-----------------------	-----------------------------

**Material data**

Fire load	0 MJ
Weight	49.3 g

### Environmental requirements

Ambient temperature (operation)	-25 ... +80 °C
---------------------------------	----------------

### Commercial data

PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143726924
Customs tariff number	85366990990

### Product Classification

UNSPSC	39121413
ETIM 9.0	EC002635
ETIM 10.0	EC002635
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance






##### Compliance Search

Environmental Product  
Compliance  
787-6716/9400-000



### Documentation

#### Bid Text

787-6716/9400-0000	19.02.2019	xml 3.40 KB	
787-6716/9400-000	12.06.2019	docx 16.66 KB	
787-6716/9400-000	12.06.2019	pdf 65.18 KB	
787-6716/9400-0000	12.06.2019	doc 29.50 KB	
787-6716/9400-0000	12.06.2019	docx 16.63 KB	
787-6716/9400-0000	12.06.2019	pdf 65.22 KB	