


Threefold faceplate, horizontal 71 mm centre distance, for two double and a single switch function, Niko Toggle alu gold brushed

227-57704

CE

4 year warranty

The Niko Toggle threefold horizontally oriented faceplate clicks onto two double and a single switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is 6 mm thick and the lower frame 2 mm.



Niko recommends a design combination with a finishing set in the following colour: alu gold.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for two double and a single switch function, Niko Toggle alu gold brushed.

- Threefold faceplate for three switches.
- Colour faceplate: alu gold brushed
- Colour RAL (approximately): 1000
- Colour NCS (approximately): NCS S 3020-Y
- Recommended colour central plate: alu gold
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled gold
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Recess for indication led:
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic

- the light guide transports the light from the optional LED to the lever
- please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 225 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 225 mm
- Marking: EU