Concord

RAXA UGR19 600 CRI95 3000K WHITE 2016445

















Features

 Raxa presents a refined solution for lighting needs, combining aesthetic finesse with functional excellence Raxa is a modular linear track system, easy and fast to install on 3-circuit tracks Specific track adaptor that guarantees a safe electrical connection Aluminum body with a slim profile, 32mm only, neat and seamless installation on OneTrack UGR19 lenses, light beam angle:68° Textured white finishing colour. Light color temperature: 3000K, warm white, Total system power: 10.6W, Fixture lumen output: 825lm, efficacy: 78lm/ W, Ra90 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation, low flicker, non-dimmable driver Suitable for installation on 3-circuit tracks, please check compatibility list. COMPATIBLE WITH OneTrack, Lytespan Round, Lytespan H-Track. Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Nominal product dimensions: L.585mmx32mmx75mm

Product Overview

Product name	RAXA UGR19 600 CRI95 3000K WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries, Office, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	825
Luminaire efficacy (lm/W)	78
Correlated colour temperature (k)	3000
Light colour	Warm White




Concord

RAXA UGR19 600 CRI95 3000K WHITE **2016445**

Colour Variation Initial (SDCM)3Beam Angle (°)68Glare control< 19	CRI (Ra)	95
Glare control < 19 Photobiological Risk Group RG0 Total power consumption (W) 10.6 Electrical protection Class I Control gear type LED driver constant current Dimmable No Housing colour White IP rating IP20 IK rating IK02	Colour Variation Initial (SDCM)	3
Photobiological Risk GroupRG0Total power consumption (W)10.6Electrical protectionClass IControl gear typeLED driver constant currentDimmableNoHousing colourWhiteIP ratingIP20IK ratingIK02	Beam Angle (°)	68
Total power consumption (W) Electrical protection Control gear type LED driver constant current No Housing colour IP rating IK rating IN02	Glare control	< 19
Electrical protectionClass IControl gear typeLED driver constant currentDimmableNoHousing colourWhiteIP ratingIP20IK ratingIK02	Photobiological Risk Group	RG0
Control gear type Dimmable No Housing colour IP rating IK rating LED driver constant current No White IP20 IK02	Total power consumption (W)	10.6
DimmableNoHousing colourWhiteIP ratingIP20IK ratingIK02	Electrical protection	Class I
Housing colour White IP rating IP20 IK rating IK02	Control gear type	LED driver constant current
IP rating IP20 IK rating IK02	Dimmable	No
IK rating IK02	Housing colour	White
	IP rating	IP20
	IK rating	IK02
Product EAN number 5025768164455	Product EAN number	5025768164455
Warranty 5 years	Warranty	5 years
Dimming method N/A	Dimming method	N/A

Photometry



Technical drawings

