

## Threefold faceplate, vertical 71 mm centre distance, for a single switch and two 45x45 functions, Niko Rocker alu gold brushed

**227-56955**



The Niko Rocker threefold vertically oriented faceplate clicks onto a single switch and two 45 x 45 mm functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker for single switch functions and Niko 45 x 45 mm finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of aluminium. The lower frame is made of white, gold coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu gold for Niko Rocker and Niko Toggle finishing sets and gold coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function



### Technical data

Threefold faceplate, vertical 71 mm centre distance, for a single switch and two 45x45 functions, Niko Rocker alu gold brushed.

- Threefold faceplate for three switches.
- Colour faceplate: alu gold brushed
- Colour RAL (approximately): 1000
- Colour NCS (approximately): NCS S 3020-Y
- Recommended colour central plate: alu gold for Niko Rocker and Niko Toggle finishing sets and gold coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upper frame is made of aluminium. The lower frame is made of white, gold coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA).

- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled gold
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 mm x 83 mm x 13 mm
- Dimensions visible (HxWxD): 225 mm x 83 mm
- Marking: EU