

Features

- Simple and slick integral design with no driver box and without any visible screws
- New technology utilization for improved performance
- Invisible in-track adaptor for an impressive architectural look
- Extremely precise light beams due to the high-quality lens
- #80mm die-cast aluminium body, Adjustable beam angle: between 10° - 50° , Textured white finishing colour
- Light color temperature: 2700 - 6500K, tunable white
- System power: 21W, Fixture lumen output: 235-760lm, efficacy: 36lm/W, Ra98 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation
- Operating voltage 220-240V / 50-60Hz, DALI suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only
- Horizontal rotation: 355°, vertical tilt: 90°
- Nominal product dimensions: D.80mmx215mm
- 5 years warranty. Suitable for track mounting


Product Overview

Product name	CONCORD BEACON MUSE TUNE DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	235-760
Luminaire efficacy (lm/W)	36


CONCORD BEACON MUSE TUNE DALI WHITE
2062907

LOR (%)	100
Light colour	Tuneable White
CRI (Ra)	98
Colour Variation Initial (SDCM)	2
Photobiological Risk Group	RG1
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	RAL9016
IP rating	IP20
IK rating	IK02
Product EAN number	5025768629077
Warranty	5 years
Dimming method	DALI

Photometry




CONCORD BEACON MUSE TUNE DALI WHITE 2062907




Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.15 0.15	E(0°) 16491 E(C90) 8.8° 8025 E(C0) 8.8° 8030
1.0	0.31 0.30	E(0°) 4123 E(C90) 8.8° 2006 E(C0) 8.8° 2006
1.5	0.46 0.45	E(0°) 1832 E(C90) 8.8° 892 E(C0) 8.8° 892
2.0	0.62 0.60	E(0°) 1031 E(C90) 8.8° 502 E(C0) 8.8° 502
2.5	0.77 0.76	E(0°) 660 E(C90) 8.8° 321 E(C0) 8.8° 321
3.0	0.93 0.91	E(0°) 458 E(C90) 8.8° 223 E(C0) 8.8° 223

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 17.2°)
— C90 - C270 (Half beam angle: 17.6°)



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.14 0.15	E(0°) 20978 E(C90) 8.0° 10233 E(C0) 8.4° 10313
1.0	0.28 0.30	E(0°) 5244 E(C90) 8.0° 2550 E(C0) 8.4° 2578
1.5	0.42 0.44	E(0°) 2321 E(C90) 8.0° 1137 E(C0) 8.4° 1146
2.0	0.56 0.59	E(0°) 1311 E(C90) 8.0° 840 E(C0) 8.4° 845
2.5	0.70 0.74	E(0°) 839 E(C90) 8.0° 409 E(C0) 8.4° 413
3.0	0.84 0.89	E(0°) 553 E(C90) 8.0° 284 E(C0) 8.4° 286

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 16.8°)
— C90 - C270 (Half beam angle: 16.0°)



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.10 0.10	E(0°) 10150 E(C90) 5.9° 9149 E(C0) 5.9° 9135
1.0	0.21 0.20	E(0°) 4540 E(C90) 5.9° 2287 E(C0) 5.8° 2284
1.5	0.31 0.30	E(0°) 2018 E(C90) 5.9° 1017 E(C0) 5.8° 1015
2.0	0.41 0.41	E(0°) 1135 E(C90) 5.9° 572 E(C0) 5.8° 571
2.5	0.52 0.51	E(0°) 728 E(C90) 5.9° 366 E(C0) 5.8° 365
3.0	0.62 0.61	E(0°) 504 E(C90) 5.9° 254 E(C0) 5.8° 254

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 11.6°)
— C90 - C270 (Half beam angle: 11.8°)

Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.09 0.10	E(0°) 22400 E(C90) 5.4° 11316 E(C0) 5.7° 11150
1.0	0.19 0.20	E(0°) 5600 E(C90) 5.4° 2829 E(C0) 5.7° 2787
1.5	0.28 0.30	E(0°) 2489 E(C90) 5.4° 1257 E(C0) 5.7° 1239
2.0	0.38 0.40	E(0°) 1400 E(C90) 5.4° 707 E(C0) 5.7° 697
2.5	0.47 0.50	E(0°) 896 E(C90) 5.4° 453 E(C0) 5.7° 446
3.0	0.57 0.60	E(0°) 622 E(C90) 5.4° 314 E(C0) 5.7° 310

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 11.4°)
— C90 - C270 (Half beam angle: 10.8°)


Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.44	E(0°) 4899 E(C0) 23.8° 1882
1.0	0.88	E(0°) 1225 E(C0) 23.8° 471
1.5	1.32	E(0°) 544 E(C0) 23.8° 209
2.0	1.76	E(0°) 308 E(C0) 23.8° 118
2.5	2.21	E(0°) 196 E(C0) 23.8° 75
3.0	2.65	E(0°) 136 E(C0) 23.8° 52

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 47.6°)
— C90 - C270 (Half beam angle: 16.0°)

Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.43 0.44	E(0°) 5543 E(C90) 23.4° 2274 E(C0) 23.7° 2264
1.0	0.87 0.88	E(0°) 1461 E(C90) 23.4° 569 E(C0) 23.7° 566
1.5	1.30 1.32	E(0°) 649 E(C90) 23.4° 253 E(C0) 23.7° 252
2.0	1.73 1.76	E(0°) 365 E(C90) 23.4° 142 E(C0) 23.7° 141
2.5	2.16 2.19	E(0°) 234 E(C90) 23.4° 91 E(C0) 23.7° 91
3.0	2.60 2.63	E(0°) 162 E(C90) 23.4° 63 E(C0) 23.7° 63

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 47.4°)
— C90 - C270 (Half beam angle: 46.8°)

Technical drawings



Data table

GENERAL DATA

Product name	CONCORD BEACON MUSE TUNE DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries, Retail
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC001744
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	235-760
Luminaire efficacy (lm/W)	36
LOR (%)	100
Light colour	Tuneable White
CRI (Ra)	98
Colour Variation Initial (SDCM)	2
Luminous Intensity (cd)	760
Distribution type	Symmetric
Photobiological Risk Group	RG1

CONCORD BEACON MUSE TUNE DALI WHITE 2062907

ELECTRICAL DATA

Total power consumption (W)	21
Current (A)	0.089
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	6.5
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	500
Inrush Current (A)	4.5
Inrush Duration (μ s)	38
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	73
Max. products per 13A C Breaker	152
Max. products per 16A C Breaker	198
Max. products per 20A C Breaker	243
Max. products per 10A B Breaker	73
Max. products per 13A B Breaker	91
Max. products per 16A B Breaker	117
Max. products per 20A B Breaker	146

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L90 B50	56650

CONCORD BEACON MUSE TUNE DALI WHITE 2062907

PHYSICAL DATA

Housing colour	RAL9016
IP rating	IP20
IK rating	IK02
Diffuser finish	Frosted
Diffuser material	Other
Reflector finish	Matt
Nominal Product Length (mm)	215
Nominal Product Width (mm)	80
Nominal Product Height (mm)	270
Nominal Product Diameter (mm)	80
Weight (kg)	0.94

PACKAGING

Product EAN number	5025768629077
Packaging single length / height (cm)	30.5
Packaging single width (cm)	13.5
Packaging single depth (cm)	20.5
DUN14 (inner)	05025768629077
Units per inner package	1
Packaging inner length / height (cm)	46.3
Packaging inner width (cm)	56.5
Packaging inner depth (cm)	0.7
Units per outer package	1
Packaging outer length / height (cm)	30.5
Packaging outer width (cm)	13.5
Packaging outer depth (cm)	20.5

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-10-35
Special purpose lamp	No
Dry applications use only	Yes

Concord

CONCORD BEACON MUSE TUNE DALI WHITE
2062907

Suitable for household illumination

No