

## AK-EK05VD: Adapter eurocone 3/4" to flat sealing



### Commercial information

Plastic transition piece to go from euro cone 3/4" to flat sealing

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 9 mm     |
| Length     | 20 mm    |
| Width      | 20 mm    |
| Net weight | 0.002 kg |

#### Certificates

#### Applications

Heating

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                               |                   |                                 |                        |
|-------------------------------|-------------------|---------------------------------|------------------------|
| Material connection 1         | Plastic (expired) | Bend radius                     | 0 Millimetre           |
| Material connection 2         | Plastic (expired) | Length                          | 20 Millimetre          |
| Reducing                      | ✗                 | Medium temperature (continuous) | -10 70 Degrees celsius |
| Eccentric                     | ✗                 | Standard Dimension Ratio (SDR)  | 0                      |
| System specific               | ✓                 |                                 |                        |
| Nominal diameter connection 2 | 3/4 inch (20)     |                                 |                        |
| Main colour fitting           | Green             |                                 |                        |
| Self-sealing                  | ✗                 |                                 |                        |
| Ring stiffness class          | Other             |                                 |                        |
| With sealing rings/gaskets    | ✗                 |                                 |                        |
| Capped                        | ✗                 |                                 |                        |
| With drain valve              | ✗                 |                                 |                        |
| FM quality mark               | ✗                 |                                 |                        |
| LPCB quality mark             | ✗                 |                                 |                        |
| ULC quality mark              | ✗                 |                                 |                        |
| UL quality mark               | ✗                 |                                 |                        |
| VdS quality mark              | ✗                 |                                 |                        |
| KIWA certified                | ✗                 |                                 |                        |
| Gastec QA mark                | ✗                 |                                 |                        |