

## 29P-1612-CS: Press-fitt adapter to copper pipe 16x12 CW724



This press fitting extended with a piece of copper pipe (50mm) is the perfect solution to switch from an existing installation in copper to a Henco solution with multiple materials.

### Commercial information

#### Basic unit dimensions

Height	22 mm
Length	92 mm
Width	22 mm
Net weight	0.061 kg

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn21Si3P (CW724R)	Outer pipe diameter connection 1	16 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	12 Millimetre
Surface treatment connection 1	Untreated	Length	92 Millimetre
Material connection 2	Copper	Length of connection 1	30 Millimetre
Material quality connection 2	Dezincification resistant brass (DZR)	Working length connection 1	30 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	50 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	50 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✘	Wrench width union nut	0 Millimetre
Eccentric	✘	Tightening torque	0 0 Newtonmetre
System specific	✓	Medium temperature (continuous)	-10 70 Degrees celsius
Connection 1	Press sleeve	Max. operating pressure at 20 °C	16 Bar
Contour code connection 1	TH	Max. operating pressure at max. medium temperature	10 Bar
Connection 2	Soldered end	Standard Dimension Ratio (SDR)	0
Contour code connection 2	V		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✘		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✘		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		