

## 13-1615A-2: Nut for eurocone,ins. and jointing ring to copper compress 16x15



### Commercial information

- Short and direct connection from brass compression fitting to Henco pipe
- Conical seal in combination with O-ring ensures a 100% guaranteed connection
- KIWA approved

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 26 mm    |
| Length     | 25 mm    |
| Width      | 26 mm    |
| Net weight | 0.051 kg |

#### Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |  |                                  |                        |
|------------------------------------|--|----------------------------------|------------------------|
| Material connection 1              | Brass  | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | CuZn40Pb2 (CW617N)                             | Outer pipe diameter connection 1 | 16 Millimetre          |
| Surface protection connection 1    | Untreated                                      | Outer pipe diameter connection 2 | 15 Millimetre          |
| Surface treatment connection 1     | Untreated                                      | Length                           | 25 Millimetre          |
| Material connection 2              | Brass  | Length of connection 1           | 12.7 Millimetre        |
| Material quality connection 2      | CuZn40Pb2 (CW617N)                             | Working length connection 1      | 12.7 Millimetre        |
| Surface protection connection 2    | Untreated                                      | Length of connection 2           | 12.5 Millimetre        |
| Surface treatment connection 2     | Untreated                                      | Working length connection 2      | 12.5 Millimetre        |
| Shape                              | Straight                                       | Wrench width                     | 0 Millimetre           |
| Reducing                           | ✘  | Wrench width union nut           | 0 Millimetre           |
| Eccentric                          | ✘  | Medium temperature (continuous)  | -10 70 Degrees celsius |
| System specific                    | ✘  | Max. operating pressure at 20 °C | 10 Bar                 |
| Connection 1                       | Compression ring                               | Standard Dimension Ratio (SDR)   | 2                      |
| Connection 2                       | Insert (push-fitting)                          |                                  |                        |
| Main colour fitting                | Brass  |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM) |                                  |                        |
| With buffer stud                   | ✓  |                                  |                        |
| High tensile strength              | ✘  |                                  |                        |
| With thermal insulation            | ✘  |                                  |                        |
| Ring stiffness class               | Other  |                                  |                        |
| With sealing rings/gaskets         | ✓  |                                  |                        |
| Capped                             | ✘  |                                  |                        |
| With drain valve                   | ✘  |                                  |                        |
| With de-aerator                    | ✘  |                                  |                        |
| FM quality mark                    | ✘  |                                  |                        |
| LPCB quality mark                  | ✘  |                                  |                        |
| ULC quality mark                   | ✘  |                                  |                        |
| UL quality mark                    | ✘  |                                  |                        |
| DIN-CERTCO certificate             | ✘  |                                  |                        |
| VdS quality mark                   | ✘  |                                  |                        |
| With approval for TÜV              | ✘  |                                  |                        |
| DVGW quality mark for gas          | ✘  |                                  |                        |
| DVGW quality mark for water        | ✘  |                                  |                        |
| KIWA certified                     | ✓  |                                  |                        |
| Gastec QA mark                     | ✘  |                                  |                        |
| KOMO certified                     | ✓  |                                  |                        |
| Type approval according to BBR/EKS | ✘  |                                  |                        |