

# Splashproof double horizontal surface-mounting socket outlet 16 A/250 Vac with shutters and pre-wired – including box with one M20 input with cable gland, screw terminals, black

## 761-37848

$\frac{h}{2}$  16 A  
250 Vac



4 year warranty

With this horizontal combination, the two splashproof surface-mounting wall sockets are equipped with side earthing, shutters and screw terminals. Both wall sockets are also equipped with a hinged protective cover and are pre-wired (2.5 mm<sup>2</sup>) and mounted in a double splashproof surface-mounting box with one M20 input with cable gland. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. .

- all connections terminals are located at the top of the base:



## Technical data

Splashproof double horizontal surface-mounting socket outlet 16 A/250 Vac with shutters and pre-wired – including box with one M20 input with cable gland, screw terminals, black. Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed

- Maximum MCB rating: 16 A (1.5 mm<sup>2</sup>) / 20 A (2.5 mm<sup>2</sup>) (limited by national installation rules)
- Number of mechanisms: 2
- Material base insert:
  - ureumformaldehyde (UF) with high heat resistance
  - white RAL9010 (approximately)
- Material finishing: the socket outlet is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS
- Material earthing: high quality brass side earthing
- Material surface-mounting box: The box is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS.
- Colour: black
- Colour RAL (approximately): 9005
- Surface treatment: coloured in mass
- Wiring space:
  - 12.7 mm wiring space under the mechanism

- mechanism is held by 2 laterally positioned holders in the box
  - a snap connector holds the wired mechanism in place
- Type of inlet: one M20 input with cable gland
- Terminal wire connection: screw terminals
- Terminals wire capacity: 4 x 2.5 mm<sup>2</sup>
- Terminals location: top of the base
- Wire stripping length: 14 mm
- Markings on the flush-mounting frame: indelibly indicated at the rear side:  
stripping length
- Type of inlet: one M20 input with cable gland
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: ÖVE
- Marking: CE