



Splashproof socket outlet 16 A with pin earthing, shutters and screw terminals, white

701-36600



This socket outlet is fitted with pin earthing, shutters, screw terminals and a hinged protection cap. The mechanism is designed to be mounted in a splashproof mounting box. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. .

- all connections terminals are located at the top of the base:



Technical data

Splashproof socket outlet 16 A with pin earthing, shutters and screw terminals, white.

- Maximum MCB rating: 16 A (1.5 mm²) / 20 A (2.5 mm²) (limited by national installation rules)
- Colour: white
- Colour RAL (approximately): 9010
- Colour NCS (approximately): NCS S 0502-Y50R
- Surface treatment: coloured in mass
- Hinged lid: Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed
- Number of lenses: 0
- Number of mechanisms: 1
- Material base insert:
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Material finishing: the socket outlet is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS
- Material earthing: solid brass nickel-plated pin earthing
- Terminal with permanent screws: each connector block is equipped with cage clamps with permanent screws
- Terminals location: top of the base
- Terminal wire connection: screw terminals
- Terminals wire capacity: 4 x 2.5 mm²
- Terminals with screw driver slot : every screw is fitted with a screwdriver slot that prevents the screwdriver from sliding off the screwhead

- Terminal screw head: combination screwhead (screw PZ2 or slot 1 x 5.5 mm)
- Wire stripping length: 14 mm
- Wiring space:
 - 15.7 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box
 - a snap connector holds the wired mechanism in place
- Wire stripping length: 14 mm
- Markings on the flush-mounting frame: indelibly indicated at the rear side: stripping length
- Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: CEBEC, NF
- Marking: CE