


Features

- Exterior LED Floodlight, comes complete with 1500mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 3000K, Non-dimming, 6300lm, 50W, 126lm/W, CRI80, Symmetrical Wide beam angle (60°), 100000 hrs L80B20 lifespan, 314 x 240 x 63mm (LxWxD) dimensions, 2.5kg weight.


Product Overview

| | |
|---------------------------------|-------------------------|
| Product name | Kalani IP66 6KLM 830 WB |
| Technology | LED |
| Cap/Base | N/A |
| E-number FI | 4579555 |
| Fixture luminous flux (lm) | 6300 |
| Luminaire efficacy (lm/W) | 126 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 50 |
| Electrical protection | Class I |
| IP rating | IP66 |
| IK rating | IK08 |
| Product EAN number | 5410288485249 |
| Warranty | 5 years |

Photometry



Technical drawings



Data table

GENERAL DATA

Product name

Kalani IP66 6KLM 830 WB

Kalani IP66 6KLM 830 WB 0048524

| | |
|---|---------|
| Technology | LED |
| Cap/Base | N/A |
| Performance ambient temperature Tq (°C) | 25 |
| E-number FI | 4579555 |
| Warranty | 5 years |

OPTICAL DATA

| | |
|---------------------------------|------------|
| Fixture luminous flux (lm) | 6300 |
| Luminaire efficacy (lm/W) | 126 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Photobiological Risk Group | RG1 |

ELECTRICAL DATA

| | |
|--|---------|
| Total power consumption (W) | 50 |
| Primary Supply/Product voltage - min (V) | 220 |
| Lamp power factor | 0.95 |
| Electrical protection | Class I |
| Control gear required | No |
| Drive current (mA) | 950 |
| Inrush Current (A) | 40 |
| Inrush Duration (µs) | 450 |
| Energy Efficiency Class (A->G) of contained light source | D |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 6 |
| Max. products per 20A B Breaker | 8 |
| Mains surge immunity (differential mode -> L-N) (kV) | 6 |
| Mains surge immunity (common mode -> L/N - GND) (kV) | 10 |

LIFETIME DATA

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 100000 |

PHYSICAL DATA

| | |
|-----------------------------|------|
| IP rating | IP66 |
| IK rating | IK08 |
| Nominal Product Length (mm) | 314 |
| Nominal Product Width (mm) | 240 |
| Weight (kg) | 2.5 |

PACKAGING

| | |
|--------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288485249 |
| Packaging single width (cm) | 11.0 |
| Packaging single depth (cm) | 28.0 |
| DUN14 (outer) | 05410288485249 |
| Packaging outer length / height (cm) | 37.0 |

SAFETY DATA

| | |
|-------------------------------------|----|
| Special purpose lamp | No |
| Dry applications use only | No |
| Suitable for household illumination | No |