

ToLEDo GLS

ToLEDo GLS 806LM 840 E27 SL4

0029639



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- 12,000 hours average rated life



PRODUCT OVERVIEW

Product name	ToLEDo GLS 806LM 840 E27 SL4
Technology	LED
Watt (Rated) (W)	8
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
ETIM Class	EC001959
Warranty	2 years
Luminous flux (lm)	806
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Wattage (W)	8
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288296395

DATA TABLE

General data

Product name	ToLEDo GLS 806LM 840 E27 SL4
Technology	LED
Watt (Rated) (W)	8

ToLEDo GLS

ToLEDo GLS 806LM 840 E27 SL4

0029639

Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	2 years

Optical data

Luminous flux (lm)	806
Luminous flux (Rated) (lm)	806
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	8
Equivalent watt (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	3.2
Inrush Duration (µs)	350
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	50
Max. products per 16A B Breaker	25

Lifetime data

Lifespan L70 B50	12000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	107
Nominal Product Diameter (mm)	60
Weight (kg)	0.114

Packaging

Single packaging type	Carton
-----------------------	--------

ToLEDo GLS

ToLEDo GLS 806LM 840 E27 SL4


0029639

Product EAN number	5410288296395
Packaging single length / height (cm)	21.2
Packaging single width (cm)	6.1
Packaging single depth (cm)	11.2
DUN14 (outer)	15410288296392
Units per outer package	6
Packaging outer length / height (cm)	37.9
Packaging outer width (cm)	22.1
Packaging outer depth (cm)	12.4


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures


PHOTOMETRY



TECHNICAL DRAWINGS



ToLEDo GLS
ToLEDo GLS 806LM 840 E27 SL4
0029639



8
kWh/1000h




ToLEDo GLS

ToLEDo GLS 806LM 840 E27 SL4

0029639



0029639



8
kWh/1000h



2019/2015