

29P-2622: Press-fitt adapter to copper pipe 26x22 CW617N



Commercial information

Henco brass press fittings: the best solution for every situation.

29P Brass (CW617N) press fitting:

- Suitable for Henco multilayer pipes measuring 16 mm in diameter
- Body material: brass (CW617N), nickel-plated
- Connection 1: press fitting, 16/20/26/32 mm
- Connection 2: solder or compression fitting, 15/22/28 mm (copper)
- Press fitting material: stainless steel
- O-ring material: EPDM
- Suitable press profiles: TH/BE for pipes measuring 16 mm in diameter
- Suitable for drinking water and heating
- Fitted with leak detection (Leak Before Press)
- Extremely pressure and temperature resistant
- Fitted with a thrust washer to prevent electrolysis
- Press fitting comes with three viewing windows

Basic unit dimensions

Net weight	0.138 kg
------------	----------

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Utility, Shipbuilding, Industry, Energy/district heating

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	26 Millimetre
Material connection 2	Copper	Outer pipe diameter connection 2	22 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Reducing	✘	Max. operating pressure at 20 °C	16 Bar
Eccentric	✘	Standard Dimension Ratio (SDR)	0
System specific	✓		
Connection 1	Press sleeve		
Contour code connection 1	TH		
Connection 2	Soldered end		
Main colour fitting	Brass		
Self-sealing	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✘		
Gastec QA mark	✘		