

Product data sheet

Item No. 96.452.7004.6

Cable assembly RST20i5KS-S 15P 70TB04

Connection cable, male - free end, length 7m, RST20i5, 5 pole, mains 250V/dimming, 16A, cable type H05VV, cross section 1,5mm², color of coding: turquoise



Item No.	96.452.7004.6
EAN	4015573941991
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends



Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	7 m
--------------	-----

Technical drawing

Kodierung/Keying 4 (250V/50V/20A)

Z

Gesamtlänge/total length: $L \pm 3\%$

Schnittlänge/cutting length: $L - 34 \pm 3\%$

all wire ends are ultrasonic welded
alle Adernenden ultrashallveredichtet

Color coding:
L: braun/brown
D2: schwarz/black
SL: gelb/grün/yellow/green
N: blau/blue
D1: grau/gray

Kabeltype/cable type H05VV-F5G1,5

Teil-Nr. part-no.	L	Beispiel (Farbe: türkisblau) example (colour: turquoiseblue)	Typ type
96.452.XXL.6	XX in dm-Schritten	96.452.1004.6 = 10dm/L = 1000mm	R512019K5-S 15P 101B04
96.452.XXL.6	XX in m-Schritten	96.452.1004.6 = 12 m/L = 12000mm	R512019K5-S 15P 112B04

96.452.1004.6	01K	a
---------------	-----	---

wieland
Konfekt-Leitungen