

127-075 WW specific configuration

LED strip | 24V | 60LED/m 5050 | 5m | IP20 | RGBW 4in1

Introduction

Purpose of this Document

This document provides information for 127-075 WW. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	4.8 W
Correlated Colour Temperature	2586 K
Total lumen output	380 lm
Efficiency	80 lm/W

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS}	24.0 V
RMS Input current feed. I_{RMS}	0.198 A
Total input power	4.8 W

Frequency of input power	0 Hz
Power factor	1.0
Displacement power factor	1.0

Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%


Input Power Curve

Voltage - Current



Efficiency


Radiated power efficiency: 25.2%



Lumen efficiency: 80 lm/W



Current Harmonics %



Harmonics

3rd Harmonic	n/a
5th Harmonic	n/a
7th Harmonic	n/a
9th Harmonic	n/a
11th Harmonic	n/a


127-075 WW specific configuration

Colour measurement details


Total lumen output 380 lm
 Correlated Colour Temperature 2586 K
 Colour coordinates CIE 1931 (x;y) = (0.469;0.411)
 Colour deviation from BBL Duv = -0.0005

TM30-18 Colour Fidelity Index R_f 87.4
 TM30-18 Colour Gamut Index R_g 95.4
 Colour Rendering Index (Ra) CRI 84.9
 Colour Rendering Index. (red component) $R_9 = 14.0$


Colour Quality Scale CQS = 84.4
 Television Lighting Consistency Index TLCI = 70



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	81	-11%	1%
C2	84	-7%	6%
C3	84	-3%	8%
C4	94	-2%	2%
C5	95	0%	2%
C6	94	1%	0%
C7	91	-4%	-3%
C8	95	-2%	1%
C9	90	-4%	4%
C10	88	-2%	7%
C11	89	3%	7%
C12	88	5%	-3%
C13	84	3%	-12%
C14	79	1%	-18%
C15	85	-5%	-8%
C16	77	-11%	-13%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale