


Splashproof bike charging station 16 A with side earthing, shutters and screw terminals, grey

700-36870



- all connections terminals are located at the top of the base:

Technical data

Splashproof bike charging station 16 A with side earthing, shutters and screw terminals, grey.

- Colour: grey
- Colour combination: light grey with green protective cover
- Colour RAL (approximately): 7035
- Colour NCS (approximately): NCS S 1502-B
- Surface treatment: coloured in mass
- Imprint indication: bike symbol
- Hinged lid: Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed
- Number of lenses: 0
- Number of mechanisms: 1
- Material base insert:
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Material finishing: the socket outlet is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS
- Material earthing: high quality brass side earthing
- Terminal with permanent screws: each connector block is equipped with cage clamps with permanent screws
- Terminals location: top of the base
- Terminal wire connection: screw terminals
- Terminals wire capacity: 4 x 2.5 mm²
- Terminals with screw driver slot : every screw is fitted with a screwdriver slot that prevents the screwdriver from sliding off the screwhead
- Terminal screw head: combination screwhead (screw PZ2 or slot 1 x 5.5 mm)
- Wire stripping length: 14 mm
- Wiring space:
 - 15.7 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box



- a snap connector holds the wired mechanism in place
- Wire stripping length: 14 mm
- Markings on the flush-mounting frame: indelibly indicated at the rear side: stripping length
- Recess for indication led:
 - the base is provided with 2 rectangular recesses for an optional lighting unit
 - left recess (front view): optional lighting unit with wires can be clicked in
- Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: ÖVE, DEKRA
- Marking: CE