

Threefold faceplate, vertical 71 mm centre distance, for a single switch and two 45x45 functions, Niko Toggle alu blue grey brushed

226-57955



The Niko Toggle threefold vertically oriented faceplate clicks onto a single switch and two 45 x 45 mm functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle for single switch functions and Niko 45 x 45 mm finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of aluminium. The lower frame is made of dark grey, blue grey coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu blue grey for Niko Rocker and Niko Toggle finishing sets and blue grey coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function



Technical data

Threefold faceplate, vertical 71 mm centre distance, for a single switch and two 45x45 functions, Niko Toggle alu blue grey brushed.

- Threefold faceplate for three switches.
- Colour faceplate: alu blue grey brushed
- Colour RAL (approximately): 240 30 05
- Colour NCS (approximately): NCS S 8005-R80B
- Recommended colour central plate: alu blue grey for Niko Rocker and Niko Toggle finishing sets and blue grey coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of aluminium. The lower frame is made of dark grey, blue grey coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA).

- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled blue grey
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 mm x 83 mm x 13 mm
- Dimensions visible (HxWxD): 225 mm x 83 mm
- Marking: EU