

START Surface IP44 DualTone PIR

START Surface IP44 PIR 1400lm 830/840 DualTone 0043437



Product features

Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 330mm. Besa mounting box compatible, hole distance 51mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 18W, output 1400 lumens (4000K). Supplied with integrated PIR (infra-red) sensor for automatic on-off presence control. IK03, IP44. Low maintenance with lifespan 90,000 hours L70:B50.


























PRODUCT OVERVIEW

Product name	START Surface IP44 PIR 1400lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC002892
E-number FI	4170572
Warranty	3 years
Useful luminous flux (Fuse)	1400
Fixture luminous flux (lm)	1400
Luminaire efficacy (lm/W)	78
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	18
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	High (>40%)
Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434377

PHOTOMETRY



START Surface IP44 DualTone PIR START Surface IP44 PIR 1400lm 830/840 DualTone 0043437



TECHNICAL DRAWINGS

