

Product data sheet

Item No. 96.453.2033.1

Cable assembly RST20I5KSB- 25 20SW

Connection cable, female - free end, length 2m, RST20i5, 5 pole, 250/400V, 20A, cable type H07RN-F, cross section 2,5 mm², color of coding: black



Item No.	96.453.2033.1
EAN	4015573918276
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	13.5 mm
Version of cable	Female - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

Kodierung/Keying 0 (250V/20A)

X

L1: braun/brown
L2: schwarz/black
SL: gelb/grün/yellow/green
N: blau/blue
L3: grau/grey

all wire ends are ultrasonic welded
alle Adernenden
ultraschallverdichtet

Schnittlänge/cutting length

Kabeltype/cable type H07RN-F5G2,5

Farbe/color	.F
schwarz/black	.I
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.453.XX33.1	XX in dm-Schritten	96.453.1033.1 = 10dm/L = 1000mm	RST201SKSB-25 106M
96.453.XX33.0		96.453.1033.0	RST201SKSB-25 106L
06.453.XX33.1	XX in m-Schritten	06.453.1233.1 = 12 m/L=12000mm	RST201SKSB-25 X125M
06.453.XX33.0		06.453.1233.0	RST201SKSB-25 X125L

96.453.XX33.1	1	96.453.1033.0 01K
---------------	---	-------------------

wieland

KONFEKT_LEITUNG