


RANA Linear Surface&Suspended - Opal Diffuser

RANA LINEAR S 32 4K OPAL SSC01 W
0051343



Product features

- Surface or Suspended LED Linear luminaire with Opal Optic, Dimensions: 1150mm x 87mm x 87mm, Direct, White Body, SylSmart Standalone capable, Electric Class 1, Neutral White LED (4000K), 3270lm, 32W, 102lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/- 5%), UGR<23, L90B10 at 50,000 hours, Glow Wire Test 850°C




PRODUCT OVERVIEW

Product name	RANA LINEAR S 32 4K OPAL SSC01 W
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3270
Fixture luminous flux (lm)	3270
Luminous flux (lm)	3270
Luminaire efficacy (lm/W)	102
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0
Total power consumption (W)	32
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288513430

RANA Linear Surface&Suspended - Opal Diffuser

RANA LINEAR S 32 4K OPAL SSC01 W
0051343

PHOTOMETRY



TECHNICAL DRAWINGS

