

CU-REGC-RF: Thermostat Lcd, Optional Ext. Sensor, Incl. 2x AAA batt



Commercial information

Thermostat LCD, optional ext. sensor

Basic unit dimensions

Height	27 mm
Length	85 mm
Width	85 mm
Net weight	0.130 kg

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Regulation type on/off	✗	Measuring range	0 40 Degrees celsius
Regulation type modulating	✓	Number of heater outputs	1
Communications protocol	Brand-dependent	Number of cooler outputs	1
Type of power supply	Battery	Differential value	2 2 Kelvin
Connection	Wireless	Number of switching programmes	4
With receiver	✓	Max. contact voltage	0 Volt
External sensor	✗	Max. contact load	0 Ampere
With thermal feedback	✗	Width	85 Millimetre
Control characteristic	Other	Depth	85 Millimetre
Suitable for heating	✓	Height	27 Millimetre
Suitable for heating	✓	Standby power consumption (solstandby)	0 Watt
Suitable for cooling	✓		
Adjustable differential	✓		
Selector switch for heating and heating with hot water	✗		
Sensor/feeler type	Resistance sensor		
Temperature readable	✓		
Relative humidity (RH) readable	✗		
With display	✓		
Type of clock	Week clock		
Clock model	Digital		
Overtime switch	✗		
Optimisation	✗		
With tap water circuit	✗		
Operation	Button		
Weather-dependent control system	✗		
Contact type	Normally open contact (NO)		
Degree of protection (IP)	IP20		
Degree of protection (NEMA)	3		
Explosion-proof	✓		
Colour	White		
Compatible with Apple HomeKit	✗		
Compatible with Google Assistant	✗		
Compatible with Amazon Alexa	✗		
IFTTT support available	✗		