

Optix Surface 1500 Asymmetric


OPTIX SURFACE 1500 ASYMMETRIC 4000K

2021734



Product features

- OPTIX SURFACE 1500 ASYMMETRIC 4000K is a surface or wall mounted LED Linear luminaire with Asymmetric Aluminium Reflector, Asymmetric Light Distribution, Luminaire Dimensions: 1480x200x50mm, Sylvania White body colour, IP20, IK07, Constant Current, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 4250lm, 37W, 115lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, lifespan: 58,000 hours L90B10.



PRODUCT OVERVIEW


Product name	OPTIX SURFACE 1500 ASYMMETRIC 4000K
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Office
ETIM Class	EC002892
E-number FI	4262045
Warranty	5 years
Fixture luminous flux (lm)	4250
Luminous flux (lm)	4250
Luminaire efficacy (lm/W)	115
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG0
Total power consumption (W)	37
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768217342

PHOTOMETRY

Optix Surface 1500 Asymmetric

OPTIX SURFACE 1500 ASYMMETRIC 4000K

2021734



TECHNICAL DRAWINGS

