

Product data sheet

Item No. 91.941.3053.0

Female connector with strain relief GST15I4S B1
ZW1V WS

Connector GST15I4, 4 pole, female, screw connection,
250/400V/16A, color of coding: white, color of housing: white



Item No.	91.941.3053.0
EAN	4015573934559
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated voltage 2	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Connection Data

Cable diameter	11.5 mm
Cable diameter 2	6 mm
Connection cross section solid	1.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	1.5 mm ²

Cross section stranded 2	0.5 mm ²
Terminations per pole	1

Model

Model	female
Number of poles	4
Connection type	Screw connection
Degree of protection (IP)	IP40

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	63 mm
Width	32.6 mm
Height	15 mm

Technical drawing

