



Item No: 2021705

Dimensions (mm)



0.5	0.70 0.68		E_{D1} E(C50) 35.1° E(C0) 34.4°	1138 312 321	
1.0	1.41 1.37		E_{D1} E(C50) 35.1° E(C0) 34.4°	264 79 80	
1.5	2.11 2.06		E_{D1} E(C50) 35.1° E(C0) 34.4°	126 54 55	
2.0	2.81 2.74		E_{D1} E(C50) 35.1° E(C0) 34.4°	71 19 20	
2.5	3.51 3.42		E_{D1} E(C50) 35.1° E(C0) 34.4°	42 12 13	
3.0	4.22 4.11		E_{D1} E(C50) 35.1° E(C0) 34.4°	31 8 9	
Distance [m]	Cone diameter [m]				Illuminance [lx]
	C0 - C150 (Half beam angle: 68.0°)				
	C95 - C270 (Incl. beam angle: 70.2°)				



OPTIX SURFACE 1500 MPO D 4000K DALI EM

Item No: 2021705

Concord

General data

Product name	OPTIX SURFACE 1500 MPO D 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Office
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4350
Luminous flux (lm)	4350
Luminaire efficacy (lm/W)	114
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 20
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Emergency duration (h)	3

Electrical data

Total power consumption (W)	38
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	1
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	9
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	300
Inrush Current (A)	23.1
Inrush Duration (µs)	174
Energy Efficiency Class (A->G) of contained light source	C, C(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	18
Max. products per 13A C Breaker	26
Max. products per 16A C Breaker	28
Max. products per 20A C Breaker	34
Max. products per 10A B Breaker	9
Max. products per 13A B Breaker	13
Max. products per 16A B Breaker	14
Max. products per 20A B Breaker	17
Connectable conductor cross section - Max (mm²)	1.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	71000

OPTIX SURFACE 1500 MPO D 4000K DALI EM

Item No: 2021705

Concord

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Prismatic
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	200
Nominal Product Height (mm)	50
Weight (kg)	5.7

Packaging

Product EAN number	5025768217052
Packaging single length / height (cm)	155.0
Packaging single width (cm)	9.0
Packaging single depth (cm)	21.0
DUN14 (inner)	05025768217052
Units per outer package	1
Packaging outer length / height (cm)	155.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	21.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	10-25