

Optix Recessed 1200 Asymmetric

OPTIX RECESSED 1200 ASYMMETRIC 3000K DALI

2021683



Product features

- OPTIX RECESSED 1200 ASYMMETRIC 3000K DALI is a ceiling recessed LED Linear luminaire with Asymmetric Aluminium Reflector, Asymmetric Light Distribution, Luminaire Dimensions: 1196x293x52mm, Sylvania White body colour, IP20, IK07, DALI dimmable, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3380lm, 30W, 113lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, lifespan: 58,000 hours L90B10.




PRODUCT OVERVIEW

Product name	OPTIX RECESSED 1200 ASYMMETRIC 3000K DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Office, Education
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3380
Fixture luminous flux (lm)	3380
Luminous flux (lm)	3380
Luminaire efficacy (lm/W)	113
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216833

PHOTOMETRY

Optix Recessed 1200 Asymmetric

OPTIX RECESSED 1200 ASYMMETRIC 3000K DALI
2021683



TECHNICAL DRAWINGS

