



CU-ACT-24V: Act With Cable 1M, 24V



Commercial information

Basic unit dimensions

Height	60 mm
Length	1,000 mm
Width	45 mm
Net weight	0.100 kg

Certificates

Applications

Heating, Cooling, Underfloor Heating



Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Model	Wax-filled	Cable length	1 Metre
Connection to stop valve	M30 x 1.5	Operating time	210 Second
Supply voltage	24 V AC	Stroke length	4 Millimetre
Control signal	0 - 10 V	Ambient temperature	0 60 Degrees celsius
Function	Deactivated when closed NC	Nominal power	1 Voltampere
Automatic stroke recognition	✘	Max. electric power input	1 Voltampere
Protected against overvoltage	✓	Length	1000 Millimetre
Auxiliary contacts	✘	Width	45 Millimetre
With end contacts	✘	Height	60 Millimetre
First open	✓	Diameter	44 Millimetre
With position indicator	✓		
With valve adapter	✓		
Self-adjusting travel length	✘		
Colour	White		
Degree of protection (IP)	IP54		

Related products

Product code	GTIN	Description	Image
BE26	05414764309845	Henco Jaws (universal) BE/TH-Profile 26x3	
UFH-ANC-05	05414764309845	Henco Valve 2x3/4 -M30x1,5-KV 2	
UFH-ANC-06	05414764309845	Henco Valve 2x1 -M30x1,5-KV 4,5	