



Data Sheet | Item Number: 750-332
BACnet/IP Fieldbus Coupler; 4th generation

<https://www.wago.com/750-332>



The 750-332 BACnet/IP Fieldbus Coupler connects the modular WAGO I/O System to the BACnet protocol and supports the B-BC BACnet device profile per DIN EN ISO 16484-5.

It communicates with other BACnet devices via BACnet/IP.

For each channel, appropriate BACnet objects are generated automatically for the digital and analog I/O modules that are connected to the fieldbus coupler (native server). The use of function, technology, and communication modules is not supported by the device.

Two ETHERNET interfaces and an integrated switch allow the fieldbus to be wired in a line topology, eliminating the need for additional network devices, such as switches or hubs.

The coupler is designed for fieldbus communication in both BACnet/IP and MODBUS networks.

An integrated Webserver provides user configuration options, while displaying the coupler's status information.

The 750-332 Coupler is equipped with a removable memory card slot. A memory card can be used to transfer device parameters or files (e.g., boot files) from one coupler to another. The memory card can be accessed via FTP and be used as an additional drive.

The maximum number of supported BACnet objects is 256.

BACnet networks are configured and commissioned using the Windows-compliant WAGO BACnet Configurator.

Technical data

Communications	BACnet/IP Modbus (TCP, UDP)
Device-specific	BACnet device profile: B-BC (BACnet building controller); BACnet revision: 12
Transmission rate	10/100 Mbit/s
Transmission medium (communication/fieldbus)	Twisted pair S-UTP; 100 Ω; Cat. 5; 100 m maximum cable length
Transmission performance	Class D per EN 50173
Type of memory card	SD and SDHC up to 32 GB (all guaranteed properties only valid with WAGO's memory card)
Memory Card Slot	Push-push mechanism; cover lid (sealable)
Number of modules per node (max.)	250
Number of modules without a bus extension (max.)	64
Configuration options	WAGO-I/O-CHECK BACnet Configurator Web-Based Management
Input and output process image (fieldbus) max.	1020 words/1020 words
Supply voltage (system)	24 VDC (-25 ... +30 %); via pluggable connector (CAGE CLAMP® connection)
Current consumption (5 V system supply)	440 mA
Total current (system supply)	1700 mA
Supply voltage (field)	24 VDC (-25 ... +30 %); via power jumper contacts
Input current (typ.) at nominal load (24 V)	500 mA
Power supply efficiency (typ.) at nominal load (24 V)	90 %
Isolation	500 V system/field
Number of outgoing power jumper contacts	3
Current carrying capacity (power jumper contacts)	10 A

Connection Data

Connection technology: communication/fieldbus	BACnet/IP: 2 x RJ-45; Modbus (TCP, UDP): 2 x RJ-45
Connection technology: field supply	6 x CAGE CLAMP®
Connection technology: system supply	2 x CAGE CLAMP®
Connectable conductor materials	Copper
Connection type	System/field supply
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Connection technology: device configuration	1 x Male connector; 4-pole

Physical data

Width	61.5 mm / 2.421 inches
Height	100 mm / 3.937 inches
Depth	71.9 mm / 2.831 inches
Depth from upper-edge of DIN-rail	64.7 mm / 2.547 inches

Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

Material data

Housing material	Polycarbonate; polyamide 6.6
Fire load	1.683 MJ
Weight	152.6 g
Conformity marking	CE

Environmental requirements

Ambient temperature (operation)	0 ... +55 °C
Ambient temperature (storage)	-25 ... +85 °C
Protection type	IP20
Pollution degree	2 per IEC 61131-2
Operating altitude	0 ... 2000 m / 0 ... 6562 ft
Mounting position	Horizontal left, horizontal right, horizontal top, horizontal bottom, vertical top and vertical bottom
Relative humidity (without condensation)	95 %
Vibration resistance	Per IEC 60068-2-6
Shock resistance	15g per IEC 60068-2-27
EMC immunity to interference	per EN 61000-6-2
EMC emission of interference	per EN 61000-6-3
Exposure to pollutants	per IEC 60068-2-42 and IEC 60068-2-43
Permissible H ₂ S contaminant concentration at a relative humidity 75 %	10 ppm
Permissible SO ₂ contaminant concentration at a relative humidity 75 %	25 ppm

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143888721
Customs tariff number	85371091990

Product Classification

UNSPSC	32151705
ETIM 9.0	EC001603
ETIM 10.0	EC001603
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

CAS-No.	1303-86-2 1317-36-8 7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Diboron trioxide Lead Lead monoxide
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	8a007cbb-10ce-4ffa-9800-32d33c1efb20
SCIP notification number (Belgium)	a0ea8133-6332-496d-95dc-830cd6aa5348
SCIP notification number (Bulgaria)	6a3df25c-f1b1-408c-a8cf-22cbc0fce8e3
SCIP notification number (Czech Republic)	405e39e8-6aa8-4037-ad62-90642c1789da
SCIP notification number (Denmark)	0e647a9e-16e7-4350-b215-d2c59ae8fe78
SCIP notification number (Finland)	aaea2fb4-2810-4ff6-aa4e-3df7b89ceeba
SCIP notification number (France)	f2456991-9f87-4254-9e9b-e8c735d68b0f

Environmental Product Compliance

SCIP notification number (Germany)	658c7eea-3351-4fd7-a392-17a67dc50317
SCIP notification number (Hungary)	cc297305-6f69-4107-b6a2-8cdd8fb3bc69
SCIP notification number (Italy)	b8672709-e8cc-491f-a8a3-089db063d005
SCIP notification number (Netherlands)	f58113e1-1033-442a-96ac-dfae3c2c250e
SCIP notification number (Poland)	bd9ef1f5-1043-468a-a4ca-02d9e457cd65
SCIP notification number (Romania)	c760670c-1406-4398-aadd-c44ee54d939d
SCIP notification number (Sweden)	dec60955-3ee0-4f50-8e9f-307b3abd2258

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03083
KC National Radio Research Agency	Article 58-2, Clause 3	MSIP-REM-W43-FBC750
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	-	E175199

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications



Approval	Standard	Certificate Name
BSH Bundesamt fuer Seeschifffahrt und Hydrographie	-	1104
DNV DNV GL SE	DNV-CG-0339, Aug. 2021	TAA0000194
PRS Polski Rejestr Statków	-	TE/1101/880590/23

Approvals for hazardous areas



Approval	Standard	Certificate Name
ATEX TUEV Nord Cert GmbH	EN 60079-0	TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc)
CCCEX CQST/CNEEx	CNCA-C23-01	2020312310000213 (Ex ec IIC T4 Gc)
IECEX TUEV Nord Cert GmbH	IEC 60079-0	IECEX TUN 14.0035 X (Ex ec IIC T4 Gc)
INMETRO TUV Rheinland do Brasil Ltda.	IEC 60079-0	TUV 12.1297 X
UKEx WAGO GmbH & Co. KG	EN 60079-0	UKCA_WA GO22UKEX003X_ec
UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS)	UL 121201	E198726

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 750-332



Documentation

Manual

Product Manual FC
BACnet/IP; G4 V 1.1.1
25.05.2022 pdf
5514.21 KB



System Manual Series
750/753



Compatibility Information

BACnet Protocol Imple-
mentation Conforma-
nce Statement (PICS) V 1.0.0
13.10.2021 pdf
453.33 KB



System Description

750/753 Series I/O-
System – General Pro-
duct Information pdf
953.35 KB



Overview on WAGO-I/
O-SYSTEM 750 appro-
vals pdf
770.48 KB



Bid Text

750-332 21.05.2019 xml
9.03 KB



750-332 21.05.2019 docx
22.07 KB



ausschreiben.de
750-332



Instruction Leaflet

CCC Ex (Additional in-
formation) 26.04.2023 pdf
159.76 KB



CAD/CAE-Data

CAD data

2D/3D Models 750-332



Engineering-Software

Configuration and Commissioning Software

(759-316) WAGO Ether-
net Settings / Serie 750 06.18.01.01
02.09.2021 zip
26678.54 KB



Runtime Software

Firmware

0750-0332, Feldbus-koppler BACnet/IP	V 06 18.10.2021	zip 5101.04 KB	
--------------------------------------	--------------------	-------------------	--

1 Compatible Products

1.1 Required Accessories

1.1.1 Memory card

1.1.1.1 Memory card



Item No.: 758-879/000-2108

Memory Card SD; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C

1.2 Optional Accessories

1.2.1 Communication

1.2.1.1 Communication cable



Item No.: 750-923/000-001

Configuration cable; USB connector; Length: 5 m

1.2.2 DIN-rail

1.2.2.1 Mounting accessories



Item No.: 210-196

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored



Item No.: 210-198

Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored



Item No.: 210-197

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored



Item No.: 210-114

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored



Item No.: 210-118

Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored



Item No.: 210-112

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored



Item No.: 210-113

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

1.2.3 Marking

1.2.3.1 Group marker carrier



Item No.: 750-106
Group marker carrier

1.2.3.2 Marker

Item No.: 750-100
Marker card; as a DIN A4 sheet; plain

Item No.: 2009-145/000-006
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue

Item No.: 2009-145/000-007
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray

Item No.: 2009-145/000-023
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green

Item No.: 2009-145/000-012
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange

Item No.: 2009-145/000-005
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red

Item No.: 2009-145/000-024
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet

Item No.: 2009-145
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

Item No.: 2009-145/000-002
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

Item No.: 248-501/000-006
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue

Item No.: 248-501/000-007
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray

Item No.: 248-501/000-023
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green

Item No.: 248-501/000-017
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green

Item No.: 248-501/000-012
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange

Item No.: 248-501/000-005
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red

Item No.: 248-501/000-024
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet

Item No.: 248-501
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

Item No.: 248-501/000-002
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow

1.2.3.3 Marker carrier



Item No.: 750-103
Group marker carrier

1.2.4 Shield termination

1.2.4.1 Shield clamping saddles



Item No.: 790-108
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm



Item No.: 790-208
Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm



Item No.: 790-116
Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm



Item No.: 790-216
Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm



Item No.: 790-124
Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm



Item No.: 790-220
Shield clamping saddle; 30 mm wide; 6 ... 20 mm



Item No.: 790-140
Shield clamping saddle; diameter of compatible conductor

1.2.5 System enclosure

1.2.5.1 System enclosure



Item No.: 850-825
 IP65 enclosure; Aluminium (RAL 7032);
 WxHxD (160x100x160 mm); 9 x M12, 4 x
 M20



Item No.: 850-826
 IP65 enclosure; Aluminium (RAL 7032);
 WxHxD (240x100x160 mm); 4 x M20, 4 x
 M16, 14 x M12 cable grip



Item No.: 850-827
 IP65 enclosure; Aluminium (RAL 7032);
 WxHxD (320x100x160 mm); 4 x M20, 8 x
 M16, 17 x M12 cable grip



Item No.: 850-828
 IP65 enclosure; Aluminium (RAL 7032);
 WxHxD (480x100x160 mm); 4 x M20, 10 x
 M16, 35 x M12 cable grip



Item No.: 850-826/002-000
 IP65 enclosure; Aluminium (RAL 7035);
 WxHxD (240x100x160 mm); 4 x M20, 4 x
 M16, 14 x M12 cable grip



Item No.: 850-827/002-000
 IP65 enclosure; Aluminium (RAL 7035);
 WxHxD (320x100x160 mm); 4 x M20, 8 x
 M16, 17 x M12 cable grip



Item No.: 850-828/002-000
 IP65 enclosure; Aluminium (RAL 7035);
 WxHxD (480x100x160 mm); 4 x M20, 10 x
 M16, 35 x M12 cable grip



Item No.: 850-834
 IP65 enclosure; Polyester (RAL 7032); Wx-
 HxD (164x100x164 mm); 9 x M12, 4 x M20



Item No.: 850-835
 IP65 enclosure; Polyester (RAL 7032); Wx-
 HxD (244x100x164 mm); 4 x M20, 4 x
 M16, 14 x M12 cable grip



Item No.: 850-836
 IP65 enclosure; Polyester (RAL 7032);
 WxHxD (324x100x164 mm); 4 x M20, 8 x
 M16, 17 x M12 cable grip



Item No.: 850-814/002-000
 IP65 enclosure; Sheet steel (RAL 7035);
 WxHxD (200x120x200 mm); without flan-
 ge plate



Item No.: 850-815/002-000
 IP65 enclosure; Sheet steel (RAL 7035);
 WxHxD (300x120x200 mm); without flan-
 ge plate



Item No.: 850-816/002-000
 IP65 enclosure; Sheet steel (RAL 7035);
 WxHxD (400x120x200 mm); without flan-
 ge plate



Item No.: 850-817/002-000
 IP65 enclosure; Sheet steel (RAL 7035);
 WxHxD (600x120x200 mm); without flan-
 ge plate