



## HIL-CWO

Slave 7 watt, 230 Volt surface mount led luminaire, series Hiled. Light distribution: wide (W), RAL9003 + RAL7015

### Product Information

|                 |                       |
|-----------------|-----------------------|
| Type            | HIL-CWO               |
| Catalog number  | 11170075              |
| Category_       | Escape route lighting |
| GTIN            | 05415022432121        |
| GID             | 7TCA091720R0099       |
| Serie           | Hiled                 |
| Warranty (Year) | 5                     |



### Characteristics

|   |                                     |
|---|-------------------------------------|
| Power supply system                             | Central                             |
| Continuous operation                            | Yes                                 |
| Mounting Method                                 | Ceiling;Wall                        |
| Mounting form                                   | Surface                             |
| Material housing                                | Aluminium / plastic                 |
| Colour housing                                  | White                               |
| Material  | Aluminium / polycarbonate           |
| Colour  | White                               |
| Length (mm)                                     | 326                                 |
| Width (mm)                                      | 143                                 |
| Height/depth (mm)                               | 109                                 |
| Nominal voltage (V)                             | 230                                 |
| Voltage type                                    | AC                                  |
| Monitoring equipment                            | None                                |
| With lamp                                       | Yes                                 |
| Lamp Type                                       | Led                                 |
| Lamp holder                                     | Other                               |
| Lamp power (W)                                  | 7                                   |
| Number of lamps                                 | 1                                   |
| Light output in emergency operation (lm)        | 1000                                |
| Average lifespan light source (hours)           | 60.000                              |
| Colour of light                                 | White                               |
| Colour temperature (K)                          | 6200                                |
| CRI   | 68                                  |
| Protection class                                | II                                  |
| Degree of protection (IP)                       | 65                                  |
| With remote switch connection                   | No                                  |
| Wiring system                                   | Maintained / non-maintained circuit |
| Type of indicator                               | Not applicable                      |
| Circuit   | Other                               |
| Impact strength (IK)                            | 08                                  |
| Power consumption maintained mode (W)           | 14                                  |
| Apparent power consumption maintained mode (VA) | 15,5                                |
| Nominal current (mA)                            | 54                                  |
| Inrush Current (A - 0.1ms)                      | 16                                  |
| Powerfactor                                     | 0,9                                 |
| Temperature range (°C)                          | 0 ~ +40                             |

### Article Details

|                 |                     |
|-----------------|---------------------|
| Product class   | Emergency luminaire |
| E-code          | EC001957            |
| Discount group  | 30405               |
| Harmonized code | 9405606000          |
| GLN             | 8713812000008       |

**Ordering information**

|                        |        |
|------------------------|--------|
| Orderable              | Yes    |
| Order-Unit             | Pieces |
| Minimum order quantity | 1      |
| Order Increment        | 1      |

**Supply Information**

|                                   |                 |
|-----------------------------------|-----------------|
| Weight (kg)                       | 1,700           |
| Packaging                         | Cardboard box   |
| Packaging dimensions (LxWxH) (mm) | 436 x 215 x 146 |